



Mobec-HeMoS GmbH - Öllinger Str. 6 - 89542 Herbrechtingen-Bissingen

Federn für Bilstein Federbeine

Bestellnr.	Länge	Drahtstärke	Federrate N/mm	Ausführung
F 74/6.5	74 mm	6.5 mm	35	35-74
F 74/7.0	74 mm	7.0 mm	47	47-74
F 74/7.5	74 mm	7,7 mm	60	60-74
F 74/8.0	74 mm	8,0 mm	82	82-74
F 74/8.5	74 mm	8,5 mm	109	109-74
F 204/7.0	204 mm	7,0 mm	17	17-204
F 204/7.5	204 mm	7,5 mm	25	25-204
F 204/8.0	204 mm	8,0 mm	30	30-204
F 204/8.5	204 mm	8,5 mm	37	37-204
F 204/9.0	204 mm	9,0 mm	46	46-204
F 204/10.0	204 mm	10,0 mm	72	72-204
F 235/7.0	235 mm	7,0 mm	17	17-235
F 255/7.0	255 mm	7,0 mm	17	17-255
F 255/7.5	255 mm	7,7 mm	25	25-255
F 255/8.0	255 mm	8,0 mm	30	30-255
F 255/8.5	255 mm	8,5 mm	37	37-255
F 255/9.0	255 mm	9,0 mm	46	46-255
F 255/10.5	255 mm	10,5 mm	70	70-255
F 255/11.0	255 mm	11,0 mm		
F 275/7.0	275 mm	7,0 mm	17	17-275
F 275/7.5	275 mm	7,7 mm	25	25-275
F 275/8.0	275 mm	8,0 mm	30	30-275
F 275/8.5	275 mm	8,5 mm	37	37-275
F 275/9.0	275 mm	9,5 mm	45	45-275
F 275/10	275 mm	10,0 mm	65	65-275